

Drift filters

FKS 05, 1, 2 - Technical data

Type	FKS 05	FKS 1	FKS 2
Filtre area:			
- basic (m ²)	0,5	1	2
- after silting-up (m ²)	0,6	1,2	2,4
Max. operatial pressure (Mpa)	0,6		
Capacity of filter body (liter)	23	42	96
Number filtration candle (piece)	4	7	14
Activ silt capacity (liter)	12 (8)*	20,5 (16)*	47,5 (32)*
Volumetric power output:			
- beer (hl/hour)	2,5 - 4	5 - 8	10 - 16
- wine (hl/hour)	5 - 15	10 - 30	20 - 60
Quantity kieselguhr ** (kg)	3,6 (2,4)*	6,2 (4,8)*	14,3 (9,6)*
Capacity dising (liter)	25	25	40
Entry/Exit	DN 25		
Lenght l (mm)	850	850	1050
Widht w (mm)	700	700	750
Height h (mm)	1 650	1 650	1 700
Material	Stainless steels 1.4301, AISI 316		
Supposed batch worked at one filtration cycle ** (hl)			
Type	FKS 05	FKS 1	FKS 2
Dosage 50 g/hl	60(32)*	100(70)*	230(140)*
Dosage 100 g/hl	30(18)*	50(35)*	115(70)*
Dosage 150 g/hl	20(12)*	33(23)*	78(47)*

